

0.4mm wall thickness PU steel wire hose, lightweight and wear-resistant

Product images	Application	Characteristic	Structure
	► Suction of crushed material particles	► Soft and easy to bend	► Color: Transparent
	► Extract dust and sawdust	► Stretch flexibly	► Temperature: -40/+90 ° C
	► Vacuum suction and exhaust	► Compressible (compression ratio 1:4)	Can reach +125 °C in a short time
	► Ventilation and dust collection	► Good wear resistance	► Connection method:
	► Machine protection sleeve	► Ozone resistant, aging resistant, mineral oil resistant	right-handed spiral
► Hose wall: Polyester polyurethane		► No softener, halogen-free	bridge clamp 991R
► Reinforcement: Copper plated steel wire reinforcement			
► There are polyether polyurethane (Ether PU) products available for selection			

Part Number	Internal diameter mm	Wall thickness mm	Weight g/m	Vacuum bar	Bending radius mm	Roll length m	Volume m ³
901-038-10	38	0.40	160	0.04	20	10	0.004
901-040-10	40	0.40	165	0.04	22	10	0.004
901-045-10	45	0.40	175	0.04	23	10	0.005
901-050-10	50	0.40	195	0.04	25	10	0.006
901-060-10	60	0.40	240	0.04	30	10	0.009
901-065-10	65	0.40	250	0.04	32	10	0.009
901-070-10	70	0.40	360	0.04	35	10	0.011
901-075-10	75	0.40	390	0.04	38	10	0.013
901-080-10	80	0.40	410	0.04	40	10	0.014
901-090-10	90	0.40	450	0.04	45	10	0.018
901-100-10	100	0.40	510	0.03	50	10	0.024
901-110-10	110	0.40	560	0.03	55	10	0.029
901-115-10	115	0.40	580	0.03	55	10	0.031
901-120-10	120	0.40	610	0.03	60	10	0.034
901-125-10	125	0.40	640	0.03	64	10	0.038
901-130-10	130	0.40	660	0.02	65	10	0.040
901-140-10	140	0.40	710	0.020	70	10	0.046
901-150-10	150	0.40	760	0.020	75	10	0.052
901-160-10	160	0.45	880	0.02	80	10	0.067
901-170-10	170	0.45	910	0.02	85	10	0.072
901-180-10	180	0.45	990	0.02	90	10	0.083
901-200-10	200	0.45	1,100	0.01	100	10	0.101
901-220-10	220	0.45	1,200	0.010	110	10	0.116
901-225-10	225	0.45	1,250	0.010	114	10	0.129
901-250-10	250	0.50	1,300	0.010	125	10	0.154
901-254-10	254	0.50	1,450	0.01	140	10	0.190
901-280-10	280	0.50	1,450	0.01	140	10	0.190
901-300-10	300	0.50	1,550	0.01	150	10	0.218
901-305-10	305	0.50	1,610	0.01	170	10	0.220
901-350-10	350	0.50	1,820	0.01	175	10	0.293
901-356-10	356	0.50	1,890	0.01	180	10	0.315
901-400-10	400	0.50	2,070	0.01	200	10	0.379
901-500-10	500	0.50	2,600	0.01	230	10	0.400

Note: * All technical parameters are approximate values and measured under conditions of 23 °C operating temperature and 50% ambient humidity. They may change accordingly based on actual operating conditions.

* We will periodically revise or adjust the relevant parameters. If we are unable to notify in a timely manner, please forgive us and refer to the data published on the website or company.