

0.7mm wall thickness PU steel wire reinforced hose with smooth inner wall

Product images	Application	Characteristic	Structure
	▶ Particle debris transportation	▶ Smooth inner wall	▶ Color:transparent
	▶ Dust and sawdust transportation	▶ Easy to bend in quality	▶ Temperature: -40/+100℃
	▶ Vacuum suction and exhaust	▶ Good wear resistance	Can reach+125℃ in a short time
	▶ Ventilation and vacuum cleaning	▶ Good airtightness	▶ Connection method:
	▶ Cable protection sleeve	▶ Good UV resistance	Right-hand spiral
▶ Hose wall: Polyester polyurethane		▶ No softener	Bridge clamp 991R 
▶ Reinforcement: Plastic coated steel wire reinforcement		▶ Ozone resistant and aging resistant	

Part Number	Internal diameter mm	Wall thickness mm	Weight kg/m	Bending radius mm	Working pressure bar	Vacuum bar	Coil length m
905D-020-20	20	0.70	0.18	30	2.04	0.45	20
905D-025-20	25	0.70	0.19	35	2.03	0.43	20
905D-030-20	30	0.70	0.25	40	1.65	0.41	21
905D-032-20	32	0.70	0.27	43	1.58	0.40	22
905D-035-20	35	0.70	0.29	47	1.34	0.38	23
905D-038-20	38	0.70	0.31	50	1.34	0.38	24
905D-040-20	40	0.70	0.33	52	1.03	0.36	25
905D-045-20	45	0.70	0.37	57	1.14	0.34	26
905D-050-20	50	0.70	0.39	62	1.02	0.32	27
905D-051-20	51	0.70	0.40	63	1.02	0.32	28
905D-055-20	55	0.70	0.44	68	0.93	0.29	29
905D-060-20	60	0.70	0.48	74	0.86	0.25	30
905D-063-20	63	0.70	0.50	76	0.80	0.23	31
905D-065-20	65	0.70	0.52	79	0.77	0.22	32
905D-070-20	70	0.70	0.56	85	0.73	0.18	33
905D-075-20	75	0.70	0.58	89	0.69	0.17	34
905D-076-20	76	0.70	0.59	90	0.69	0.17	35
905D-080-20	80	0.70	0.64	96	0.64	0.15	36
905D-085-20	85	0.70	0.68	101	0.60	0.14	37
905D-090-20	90	0.70	0.72	107	0.57	0.13	20
905D-102-15	102	0.70	0.80	118	0.52	0.10	15
905D-110-15	110	0.70	0.87	129	0.47	0.10	15
905D-115-15	115	0.70	0.90	134	0.45	0.09	15
905D-120-15	120	0.70	0.95	140	0.43	0.09	15
905D-125-15	127	0.70	0.98	145	0.41	0.07	15
905D-130-15	130	0.70	1.01	151	0.40	0.07	15
905D-140-15	140	0.70	1.09	162	0.37	0.07	15
905D-152-15	152	0.70	1.40	173	0.34	0.07	15
905D-160-15	160	0.70	1.50	184	0.34	0.06	15
905D-170-15	170	0.70	1.58	193	0.32	0.06	15
905D-175-15	175	0.70	1.63	200	0.29	0.05	15
905D-180-15	180	0.70	1.67	206	0.29	0.05	15
905D-203-15	203	0.70	1.86	228	0.26	0.05	15
905D-215-15	215	0.70	1.95	241	0.24	0.04	15
905D-228-10	228	0.70	2.08	255	0.23	0.03	10
905D-254-10	254	0.70	2.31	283	0.20	0.02	10
905D-275-10	275	0.70	2.54	310	0.19	0.02	10
905D-280-10	280	0.70	2.61	320	0.18	0.02	10
905D-300-10	300	0.70	2.77	338	0.17	0.02	10

Note: * All technical parameters are approximate values and measured under conditions of 23 °C operating temperature and 50% ambient humidity. They may change accordingly based on actual operating conditions.

* We will periodically revise or adjust the relevant parameters. If we are unable to notify in a timely manner, please forgive us and refer to the data published on the website or company.